

Photometric Data SPACING TABLES

Corridor		1 Lux floor luminosity				Open Areas	0.5 Lux floor luminosity			
MODEL	Height (metre)					MODEL				
GR-1310/4P	2.0	3.20	7.80	3.00	7.30	GR-1310/4P	3.90	9.30	3.60	8.80
	2.5	3.60	8.70	3.30	8.20		4.30	10.40	4.10	9.80
	2.7	3.70	9.10	3.40	8.40		4.50	10.80	4.20	10.20
	3.0	3.90	9.50	3.60	8.80		4.70	11.40	4.40	10.70
	3.5	4.10	10.20	3.80	9.40		5.10	12.30	4.70	11.50
	4	4.30	10.80	3.90	10.00		5.40	13.20	5.00	12.20
	4.5	4.40	11.30	4.00	10.40		5.60	13.90	5.20	12.90
	5	4.40	11.70	4.10	10.80		5.80	14.50	5.40	13.40
	5.5	4.40	12.10	4.10	11.10		6.00	15.10	5.50	14.00
	6	4.40	12.30	4.10	11.30		6.10	15.70	5.60	14.40
	7	4.00	12.60	3.90	11.70		6.30	16.60	5.80	15.20
	8	3.40	12.50	3.30	11.80		6.20	17.20	5.90	15.80
	9.5	3.00	11.80	3.00	11.40		5.90	17.70	5.70	16.40
	10	-	-	-	-		5.60	17.80	5.50	16.50
	11						5.00	17.80	4.90	16.70
	13						3.00	17.10	3.00	16.30
14					-	-	-	-		