

# Photometric Data SPACING TABLES

Corridor		1 Lux floor luminosity				Open Areas	0.5 Lux floor luminosity			
MODEL	Height (metre)					MODEL				
GR-1315/15L	2.0	2.90	6.10	2.90	6.10	GR-1315/15L	3.00	7.00	3.00	7.00
	2.5	3.00	6.40	3.00	6.40		3.20	7.80	3.20	7.80
	2.7	3.00	6.60	3.00	6.60		3.30	8.10	3.30	8.10
	3.0	3.00	6.90	3.00	6.90		3.40	8.50	3.40	8.50
	3.5	3.00	7.20	3.00	7.30		3.60	9.00	3.60	9.10
	4	3.00	7.40	3.00	7.60		3.70	9.50	3.80	9.60
	4.5	3.00	7.60	3.00	7.80		3.80	9.90	3.90	10.00
	5	3.00	7.60	3.00	7.90		3.80	10.30	3.90	10.40
	5.5	3.00	7.50	3.00	7.80		3.70	10.50	3.90	10.70
	6	3.00	7.20	3.00	7.70		3.60	10.70	3.80	10.90
	7	-	-	-	-		3.10	10.70	3.50	11.10
	8						3.00	10.50	3.00	11.10
	9						3.00	9.80	3.00	10.70
	10						-	-	-	-