

Photometric Data SPACING TABLES

Corridor		1 Lux floor luminosity				Open Areas	0.5 Lux floor luminosity			
MODEL	Height (metre)					MODEL				
GR-1315/6P	2.0	3.10	7.50	3.00	7.40	GR-1315/6P	3.70	8.90	3.70	8.90
	2.5	3.50	8.40	3.40	8.20		4.20	10.00	4.10	9.90
	2.7	3.60	8.70	3.50	8.50		4.30	10.40	4.20	10.30
	3.0	3.80	9.20	3.60	9.00		4.60	10.90	4.50	10.80
	3.5	4.10	9.90	3.90	9.60		4.90	11.80	4.80	11.60
	4	4.30	10.60	4.10	10.20		5.30	12.70	5.10	12.40
	4.5	4.50	11.10	4.20	10.60		5.50	13.40	5.30	13.10
	5	4.60	11.70	4.30	11.10		5.80	14.10	5.50	13.70
	5.5	4.70	12.10	4.40	11.50		6.00	14.80	5.70	14.20
	6	4.80	12.50	4.50	11.80		6.20	15.40	5.90	14.70
	7	4.80	13.10	4.40	12.30		6.50	16.40	6.10	15.60
	8	4.60	13.50	4.30	12.60		6.70	17.30	6.30	16.40
	9	4.20	13.70	3.90	12.70		6.80	18.00	6.30	17.00
	10	3.50	13.60	3.30	12.60		6.80	18.60	6.30	17.50
	11	3.00	13.30	3.00	12.30		6.60	19.00	6.10	17.80
	12	-	-	-	-		6.30	19.30	5.90	18.00
14					5.10	19.20	4.80	17.90		
16					3.00	18.60	3.00	17.20		