

Photometric Data SPACING TABLES

Corridor		1 Lux floor luminosity				Open Areas	0.5 Lux floor luminosity			
MODEL	Height (metre)					MODEL				
GR-1938/6P	2.0	3.30	7.50	3.30	7.90	GR-1938/6P	3.70	8.70	3.90	9.60
	2.5	3.70	8.70	3.60	8.80		4.30	10.00	4.40	10.60
	2.7	3.90	9.10	3.70	9.10		4.50	10.40	4.50	11.00
	3.0	4.10	9.70	3.90	9.50		4.80	11.10	4.70	11.60
	3.5	4.40	10.60	4.10	10.20		5.30	12.20	5.10	12.40
	4	4.70	11.40	4.30	10.80		5.70	13.20	5.40	13.20
	4.5	5.00	12.10	4.50	11.30		6.00	14.20	5.60	13.90
	5	5.20	12.70	4.60	11.80		6.30	15.10	5.90	14.50
	5.5	5.30	13.30	4.70	12.20		6.60	15.90	6.10	15.10
	6	5.50	13.90	4.80	12.60		6.90	16.60	6.30	15.70
	7	5.60	14.70	4.80	13.10		7.30	18.00	6.50	16.60
	8	5.50	15.30	4.70	13.60		7.60	19.10	6.80	17.40
	9	5.30	15.70	4.40	13.70		7.80	20.10	6.80	18.10
	10	4.70	15.90	4.00	13.70		7.90	20.90	6.80	18.70
	11	3.80	15.70	3.30	13.50		7.80	21.50	6.70	19.10
	12	3.00	15.40	3.00	13.00		7.70	22.00	6.50	19.40
	13	-	-	-	-		7.30	22.30	6.10	19.50
	15						6.00	22.40	5.10	19.20
17					3.10	21.80	3.00	18.40		
18					-	-	-	-		